

# CONGELATORI A POZZO

## CHEST FREEZER



### FR 200 PS K

Congelatore statico a pozzo porta cieca battente.  
Static chest freezer with solid hinged lids.



### FR 300 PS K

Congelatore statico a pozzo porta cieca battente.  
Static chest freezer with solid hinged lids.



### FR 400 PS K

Congelatore statico a pozzo porta cieca battente.  
Static chest freezer with solid hinged lids.

Pastry & Frozen



**Klimaitalia**





Chiave e serratura  
Lock and key



Regolatore di temperatura meccanico  
Mechanical controller



Ruote  
Castors



Dimensioni mm / Dimensions mm	FR 200 PS K	FR 300 PS K	FR 400 PS K
Dimensioni Esterne (LxPxH) / External Dimensions (WxDxH)	725 x 720 x 845	1015 x 720 x 845	1305 x 720 x 845
Dimensioni Imballo (LxPxH) / Packaging Dimensions (WxDxH)	780 x 760 x 990	1070 x 760 x 990	1360 x 760 x 990
A - Larghezza / Width	600	890	1180
B - Profondità / Depth	510	510	510
C - Altezza / Height	675	675	675
E - Altezza Minima / Min. Height	445	445	445
F - Larghezza Minima / Min. Width	390	680	970
Adesivo Laterale Destro / Side Right Sticker	625 x 487	625 x 487	625 x 487
Adesivo Laterale Sinistro / Side Left Sticker	625 x 750	625 x 750	625 x 750
Adesivo Frontale / Front Sticker	715 x 750	1005 x 750	1295 x 750

Caratteristiche Tecniche / Technical Features	FR 200 PS K	FR 300 PS K	FR 400 PS K
Temperatura / Temperature Range	-24 °C / -18 °C	-24 °C / -18 °C	-24 °C / -18 °C
Classe Climatica / Climate Class	4	4	4
Volume Netto-Lordo / Net-Gross Volume	Lt. 177 / 186	Lt. 275 / 288	Lt. 373 / 391
Superficie Esterna / Body	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment	Lamiera preverniciata con trattamento anticorrosione Prepainted sheet with anticorrosion treatment
Superficie Interna / Inner Liner	Alluminio martellato Embossed Aluminium	Alluminio martellato Embossed Aluminium	Alluminio martellato Embossed Aluminium
Cestelli / Baskets	Optional (max 2 pz / max 2 pcs)	Optional (max 3 pz / max 3 pcs)	Optional (max 5 pz / max 5 pcs)
Termometro / Thermometer	Analogico / Analogue	Analogico / Analogue	Analogico / Analogue
Regolatore temperatura / Controller	Meccanico / Mechanical	Meccanico / Mechanical	Meccanico / Mechanical
Rumorosità / Noise level	dB 40	dB 40	dB 40
Spessore isolamento / Insulation thickness	mm 60	mm 60	mm 60
Sbrinamento / Defrost	Manuale / Manual	Manuale / Manual	Manuale / Manual
Illuminazione coperchio / Lid lighting	Si / Yes	-	-
Chiave e serratura / Lock and key	Si / Yes	Si / Yes	Si / Yes
Ruote-Piedi / Castors-Feet	4 Ruote / 4 Castors	4 Ruote / 4 Castors	4 Ruote / 4 Castors
Peso Netto-Lordo / Net-Gross Weight	Kg 43 / 48	Kg 50 / 58	Kg 58 / 68
Voltaggio / Voltage	V 220-240	V 220-240	V 220-240
Frequenza / Frequency	Hz 50	Hz 50	Hz 50
Refrigerante / Refrigerant	R600A	R600A	R600A
Assorbimento / Absorption	W 171	W 193	W 257
Consumo Energia / Energy Consumption	KwH/24H 1,31	KwH/24H 1,65	KwH/24H 1,99